



LED Panel Light



Features:

- Slim body 9mm thickness.
- 0-10V dimming ,PWM,and Dali at option.
- High lumen efficiency 135lm/W.
- Great uniformity, no dark zone.
- Optional emergency power supply.



Type A: Standard







Type B: Emergency power supply

Application

Offices, Schools, Sospitals, Government buildings and Residential.

Technical Specification

| Item No. | KBSPL020 | KBSPL030 | KBSPL035A | KTXPL050 |
|----------------------------|---|--|---|---|
| Ref.Photo |  |  |  |  |
| Nominal Power (W) | 20 | 30 | 35 | 50 |
| Input Voltage (V) | AC100-277V | | | |
| Luminous Efficiency (lm/W) | 135lm/W | | | |
| Lumen Output (lm) | 2800 | 4100 | 5000 | 6500 |
| LED Light Source | Epistar | | | |
| CCT (K) | 3000-6000 | | | |
| CRI | > 80 | | | |
| Power Factor | 0.9 | | | |
| Dimmable | 0-10V dimmable | | | |
| Beam Angle | 120° | | | |
| IP Rating | IP20 | | | |
| Body Material | Aluminum | | | |
| Lifetime(Hrs) | 50000 | | | |
| Dimension(ft) | 2*2ft | 2*2ft | 2*4ft | 2*4ft |
| Warranty | 5 Years | | | |
| Certification | UL/DLC | | | |
| Working Temperature | -20°C ~ 45°C | | | |