

Athina LED Linear Bay Light



Features:





- Neat and cutting-edge design, bring great integrity to the building.
- High luminaire efficiency up to 135lm/W.
- Typical modular design, big power range from 60W-240W, easy for maintenance.
- Multiple dimming control options: 0/1-10V dimming, RX, Dali, PWM, External/Internal Microwave sensor, Day light sensor.
- Fully equipped accessories, includes Hanging bucket, Ceiling wall/Adjustable bracket, Control systems, Suspension chains, Waterproof connectors.
- 5 & 10 years warranty.



Application

Warehouse, Production facilities, Logistic centers, Exhibition centers.

Technical Specification

Content	KOFLH060	KOFLH120	KOFLH180	KOFLH240
Ref.Photo				
Nominal Power (W)	60	120	180	240
Input Voltage (V)	NA: AC100-277V EU:100-240VAC			
Luminous Efficiency (lm/W)	120-135lm/W			
Lumen Output (lm)	8100	16200	24300	32400
LED Light Source	Lumileds or equivalent			
CCT (K)	2700-6000K			
CRI	>80			
Power Factor	0.95			
Driver	Meanwell			
Beam Angle	135*70° / 90*90°			
IP Rating	IP65			
Body Material	Aluminum			
Lifetime(Hrs)	50000			
Dimension(mm)	340*140*115mm	640*140*115mm	930*140*115mm	1230*140*115mm
Warranty	5-10 Years			
Certification	ETL/DLC/CE/CB			
Working Temperature	-30℃ ~ 60℃			

Accessories



OHD-PMS-SC
Hanging buckle+Suspension chains
Suspension chains:0.3m
(stainless steel)



OHD-PMS-WB01
Ceiling wall bracket



OHD-PMS-WB02
Ceiling wall
adjustable bracket



OHD-PMS-MS01
IP65 Microwave sensor
Outside



OHD-PMS-MS02
IP65 Microwave sensor
Inside



OHD-PA-DS01
Daylight sensor



OHD-PA-WC2
waterproof connect
2M



OHD-PA-WC5
waterproof connect
5M



OHD-PA-SC
Suspension chains